



المصرية للتجارة و الخدمات الفنية  
El Masria for Trade &Tech. services



# SUB-JET 1902



## 2-Head High Speed Digital Sublimation Printer

I3200 - A1 2H

TOP SPEED 60 m<sup>2</sup>/h

Sublimation Ink



# SUB-JET 1902

## 2-Heads High Speed Digital Sublimation Printer

### Technical Characteristics

- Original i3200 print head, more durable and stable.
- Felt roller to ensure smoother paper feeding.
- 2 pcs heads configuration, higher productivity.
- Professional color management software, more accurate output color.
- Bold structure brings more stable long-term printing.
- Fully sealed drying system and mute fans reduce noise a lot.
- State-of-art industrial design concept, strong body.

### Technical Specifications

<b>Model</b>	<b>SUB-JET 1902</b>	
Print Head	Two I3200 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	72 in.(1830 mm)
	Thickness	Maximum 39 mil(1 mm)
	Maximum Media Load	500m
Printing Width	70.8 in.(1800 mm)	
Ink Cartridges	Type	Dye Sublimation Ink
	Color	4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 3600 dpi	
Rip Software	Ergosoft / Neostampa	
Printing Speed	3 pass /60m <sup>2</sup> /h	
	4 pass /40m <sup>2</sup> /h	
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system	
Interface	USB 3.0	
Power Supply	AC 220V ± 10%. 50/60 HZ	
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	

Machine Dimension: L3160mm\*W960mm\*H1860mm

Machine Box: L3530mm\*W760mm\*H855mm

Net Weight: 300KG

Rated current: 32A/554

Rated voltage: AC 220-240 V/100-120 V

Rated power: 430W+2400W

